


## WXX802 Wall Speaker

## Features

- Powerful 2-way wall speaker
- True-to-nature sound reproduction
- Available in 3 different colours
- Vertical or horizontal mounting
- Mounting bracket is included
- Easy installation
- Aluminium grill
- Adjustable power tapping

## Applications

- Wide variation of indoor applications
- Private houses
- Halls, Pubs
- Restaurants
- Stores
- Warehouses



The WX802 has a 8" low frequency loudspeaker and a 1" dome tweeter and is built in a synthetic enclosure which makes the speaker suitable for all purposes.

The speaker is suitable for standard home indoor installations to specialized indoor design appliances.

Due to the construction, the speaker can be mounted vertically or horizontally, using the included wall bracket.

This loudspeaker is available in three colours: white, black and silver, and is standard delivered with a wall fixig bracket in the same colour as the speaker.

By means of a recessed adjuster screw at the rear the power can be set in 3 adjustable steps of impedance for 100V and 1 step for 16 Ohm standard low impedance applications.

- 60 Watt, 30 Watt, 15 Watt @ 100V
- 70 Watt @ 16 Ohm



## **▶** Specifications

		2-Way 140 W		
RMS power Impendance		140 W		
mpendance		140 W		
		70 W		
	Impendance		16 Ohm	
Line Transformer Taps	1	60 W / 165 Ohm		
	2	30 W / 330 Ohm		
	3	15 W / 660 Ohm		
Sensitivity (1W/1m)		89 dB		
Sound Pressure Max W / 1m @ 8 Ohm		108 dB		
Sound Pressure Max W / 1m @ 100 V		106 dB		
Frequency Response (± 3 dB)		60 Hz - 17 kHz		
Frequency Range (-10 dB)		50 Hz - 20 kHz		
Cross-over Type		Passive Built-in		
Cross-over Frequency		2,4 kHz		
Horizontal Dispersion		110°		
Vertical Dispersion		110°		
PRODUCT FEATURES				
Dimensions (Width x Height x Depth)		270 x 360 x 215 mm		
Weight net		7,5 Kg		
Drivers	HF	1"		
	LF	8"		
Construction		ABS housing		
Grill Type		Aluminium grill		
Mounting & Handling		Mounting bracket		
Available Colours		White (RAL 9010)	WX802/W	
		Black (RAL 9005)	WX802/B	
		Silver (RAL 9006)	WX802/S	
SHIPPING & ORDERING				
Packaging		Carton box		
Shipping Weight & Volume		15 Kg - 0,0636 Cbm		
Accessory Included		Mounting bracket		

\*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products