

The **MHO 420 TW/EN** horn type speaker units are particularly well suited for outdoor use, even in difficult weather conditions. They feature a watertight construction and a high level of weatherproofing. The body is made of die-cast aluminium while the screws and brackets are made of stainless steel. The horn is made of

aluminium sheeting. Each model has a line transformer and a rear switch for selecting the operating output (5 steps).

The **MHO 420 TW/EN** has been designed to be used in security installations and has a thermal fuse which excludes the speaker in case of overheating, a ground connector and a flame resistant connecting cable (80 cm long).



	MHO 420 TW/EN
<b>Code</b>	<b>37735</b>
<b>Rated power</b>	20 W
<b>Adjustable power</b>	20 / 15 / 10 / 5 / 2.5 W
<b>Material</b>	Aluminium
<b>Speakers</b>	Complete with driver unit
<b>Sound press. SPL Pnom/1m</b>	123 dB
<b>Sensitivity 1W/1m</b>	110 dB
<b>Frequency response</b>	160 ÷ 10.000 Hz
<b>Dispersion angle @2kHz</b>	80°
<b>Protection degree</b>	IP 65
<b>Installation</b>	Adjustable brackets and fire resistant cable included
<b>Colour</b>	Light grey
<b>Dimensions (W x H x D)</b>	Ø 213x230 mm
<b>Weight</b>	1,8 kg